

EU-Declaration of Performance

*In accordance with Annex III of Regulation (EU) No. 305/2011
(Construction Product Regulation)*

For the product “**MARISEAL 250 / MARISEAL 250FLASH**”

1. Unique identification of the product-type:
ETAG 005 – part 6
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch number: See product label under “Batch Number”
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

ETAG 005 – part 6

Liquid applied roof waterproofing kits based on polyurethane resin

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):
**MARIS POLYMERS SA
Industrial Area of Inofita
GR-32011 / Inofita**
5. When applicable, the name and contact address of the authorized representative who has received a mandate for the tasks set out in Article 12(2):
Not relevant
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

ETAG 005 – part 6

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonized standard:

MPA Braunschweig

Beethovenstrasse 52, D-38106 Braunschweig (0761-CPD)

Tested the fire behavior (DIN EN ISO 9239-1, 11925-2, 13501-1) according to System 3:

Test reports Nr: 3770/0142-a-Fe/Wi

MPA Braunschweig

Beethovenstrasse 52, D-38106 Braunschweig, (0761-CPD)

The notified body has carried out initial inspection of the products and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 1.

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued:

ETA 05/0197

9. Declared performance:

ETAG 005 – part 6

The product is used in surface protection system **MARISEAL SYSTEM**, consisting of components:

MARISEAL AQUA PRIMER, MARISEAL 710, MARISEAL 250, MARISEAL 250FLASH,
MARISEAL 400, MARISEAL 420

Performance determined in System **MARISEAL SYSTEM**

Essential characteristics	Performance	Harmonised technical specification
Water vapour resistance value in μ	1830	ETAG 005 – part 6
Working life	W2 and W3	ETAG 005 – part 6
Climatic zones	M and S	ETAG 005 – part 6
Imposed loads	P1 to P4	ETAG 005 – part 6
Roof slope	S1 to S4	ETAG 005 – part 6
Lowest surface temperature:	TL4	ETAG 005 – part 6
Highest surface temperature:	TH4	ETAG 005 – part 6
Resistance to spreading fire and radiant heat:	NPD	ETAG 005 – part 6
Reaction to fire:	Class E	ETAG 005 – part 6
Statement on dangerous substances:	Does not contain any	ETAG 005 – part 6
Resistance to wind loads	> 50 kPa	ETAG 005 – part 6

NPD: No Performance Determined

When specific technical documentation in accordance with Articles 37 and 38 was used, the requirements that the product fulfills:

Not applicable

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer by:

Michail Maris
R&D Director
MARIS POLYMERS SA

Attachments:

Technical data sheets for use in and on buildings (System build up according to respective technical data sheets)